



STUDLINK CHAIN – GRADE 2

Available Galvanised or Black . Larger sizes available on request.



Code	Dia. [“d”] (mm)	Grade 2		Weight kg/ 27.5m	Weight kg/m
		Proof Load (tonne-f)	Break Load (tonne-f)		
CSL212B/G	12.5	6.7	9.4	110	4.0
CSL214B/G	14	8.4	11.8	130	4.7
CSL216B/G	16	10.9	15.3	170	6.2
CSL217B/G	17.5	13.0	18.3	180	6.5
CSL219B/G	19	15.3	21.5	220	8.0
CSL220B/G	20.5	17.8	24.9	260	9.4
CSL222B/G	22	20.4	28.6	300	10.9
CSL224B/G	24	24.2	33.9	340	12.4
CSL226B/G	26	28.3	39.7	405	14.7
CSL228B/G	28	32.7	45.8	475	17.3
CSL230B/G	30	37.5	52.4	545	19.8
CSL232B/G	32	42.5	59.4	615	22.4
CSL234B/G	34	47.7	66.8	690	25.1
CSL236B/G	36	53.3	74.6	775	28.2
CSL238B/G	38	59.3	82.8	760	31.3
CSL240B/G	40	65.3	91.4	950	34.5
CSL242B/G	42	71.7	100.0	1040	37.8
CSL244B/G	44	78.4	110.0	1130	41.1
CSL246B/G	46	85.3	119.0	1240	45.1
CSL248B/G	48	92.6	130.0	1345	48.9
CSL250B/G	50	100.0	140.0	1455	52.9
CSL252B/G	52	108.0	151.0	1575	57.3
CSL254B/G	54	116.0	162.0	1690	61.4
CSL256B/G	56	124.0	174.0	1810	65.8
CSL258B/G	58	132.0	185.0	1945	70.7
CSL260B/G	60	141.0	198.0	2075	75.4
CSL262B/G	62	150.0	210.0	2220	80.7
CSL264B/G	64	159.0	223.0	2370	86.2
CSL266B/G	66	169.0	236.0	2525	91.8
CSL268B/G	68	178.0	250.0	2685	97.6
CSL270B/G	70	188.0	263.0	2850	103.6
CSL273B/G	73	203.0	285.0	3100	112.7
CSL276B/G	76	219	307.0	3360	122.2
CSL278B/G	78	230.0	322.0	3535	128.5
CSL281B/G	81	246.0	345.0	3820	138.9
CSL284B/G	84	263.0	368.0	4105	149.3
CSL287B/G	87	280.0	393.0	4405	160.2
CSL290B/G	90	298.0	417.0	4705	171.1
CSL292B/G	92	310.0	434.0	4905	178.4
CSL294B/G	94	329.0	460.0	5210	189.4
CSL297B/G	97	341.0	477.0	5425	197.3
CSL2100B/G	100	360.0	504.0	5745	208.9
CSL2102B/G	102	373.0	522.0	5970	217.1
CSL2105B/G	105	393.0	550.0	6320	229.8
CSL2107B/G	107	406.0	568.0	6575	239.1
CSL2111B/G	111	433.0	606.0	7080	257.4
CSL2114B/G	114	453.0	635.0	7475	271.8
CSL2117B/G	117	474.0	664.0	7870	286.2
CSL2120B/G	120	495.0	694.0	8270	300.7
CSL2122B/G	122	510.0	714.0	8550	310.9
CSL2124B/G	124	524.0	734.0	8835	321.3
CSL2127B/G	127	546.0	764.0	9270	337.1
CSL2130B/G	130	568.0	795.0	9710	353.1
CSL3132B/G	132	583.0	816.0	10005	363.8

