



STUDLINK CHAIN - GRADE 3

Available Galvanised or Black . Larger sizes available on request.



Code	Dia. ['D'] (mm)	Proof Load (tonne-f)	Break Load (tonne-f)	Weight kg/ 27.5m	Weight kg/m
CSL312B/G	12.5	9.4	13.5	11	4.0
CSL314B/G	14	11.8	16.8	130	4.7
CSL316B/G	16	15.3	22.0	170	6.2
CSL317B/G	17.5	18.3	26.1	180	6.5
CSL319B/G	19	21.5	30.7	220	8.0
CSL320B/G	20.5	24.9	35.6	260	9.4
CSL322B/G	22	28.6	40.9	300	10.9
CSL324B/G	24	33.9	48.5	340	12.4
CSL326B/G	26	39.7	56.7	405	14.7
CSL328B/G	28	45.8	65.5	475	17.3
CSL330B/G	30	52.4	74.9	545	19.8
CSL332B/G	32	59.4	84.9	615	22.4
CSL334B/G	34	66.8	95.5	690	25.1
CSL336B/G	36	74.6	107.0	775	28.2
CSL338B/G	38	82.8	118.0	760	31.3
CSL340B/G	40	91.4	131.0	950	34.5
CSL342B/G	42	100.0	143.0	1040	37.8
CSL344B/G	44	110.0	157.0	1130	41.1
CSL346B/G	46	119.0	171.0	1240	45.1
CSL348B/G	48	130.0	185.0	1345	48.9
CSL350B/G	50	140.0	200.0	1455	52.9
CSL352B/G	52	151.0	215.0	1575	57.3
CSL354B/G	54	162.0	231.0	1690	61.4
CSL356B/G	56	174.0	248.0	1810	65.8
CSL358B/G	58	185.0	265.0	1945	70.7
CSL360B/G	60	198.0	282.0	2075	75.4
CSL362B/G	62	210.0	300.0	2220	80.7
CSL364B/G	64	223.0	319.0	2370	86.2
CSL366B/G	66	236.0	337.0	2525	91.8
CSL368B/G	68	250.0	357.0	2685	97.6
CSL370B/G	70	263.0	376.0	2850	103.6
CSL373B/G	73	285.0	407.0	3100	112.7
CSL376B/G	76	307.0	438.0	3360	122.2
CSL378B/G	78	322.0	459.0	3535	128.5
CSL381B/G	81	345.0	492.0	3820	138.9
CSL384B/G	84	368.0	526.0	4105	149.3
CSL387B/G	87	393.0	561.0	4405	160.2
CSL390B/G	90	417.0	596.0	4705	171.1
CSL392B/G	92	434.0	620.0	4905	178.4
CSL394B/G	94	460.0	657.0	5210	189.4
CSL397B/G	97	477.0	682.0	5425	197.3
CSL3100B/G	100	504.0	720.0	5745	208.9
CSL3102B/G	102	522.0	746.0	5970	217.1
CSL3105B/G	105	550.0	785.0	6320	229.8
CSL3107B/G	107	568.0	812.0	6575	239.1
CSL3111B/G	111	606.0	865.0	7080	257.4
CSL3114B/G	114	635.0	907.0	7475	271.8
CSL3117B/G	117	664.0	948.0	7870	286.2
CSL3120B/G	120	694.0	991.0	8270	300.7
CSL3122B/G	122	714.0	1019.0	8550	310.9
CSL3124B/G	124	734.0	1048.0	8835	321.3
CSL3127B/G	127	764.0	1092.0	9270	337.1
CSL3130B/G	130	795.0	1136.0	9710	353.1
CSL3132B/G	132	816.0	1165.0	10005	363.8

